



USER MANUAL

ANGLE GRINDERS

MODELS : FA-2C-2, -2BF, -3, -3BF



FA-2C-2BF, -3BF

FA-2C-2, -3

SPECIFICATIONS

Model	Collet Size		Max. Dia (Mounted Wheel)		Spindle Thread Size	Rotational Frequency	Angle Head Height		Overall Length		Mass		Max. Air Consumption		Air Hose Size	
	mm	in	mm	in			in	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm
FA-2C-2	6	1/4	38×13×—	1 1/2×1/2×—	3/8-24UNF(M)	15,000	90	3 35/64	157	6 3/16	0.6	1.3	0.40	14.1	9.5	3/8
FA-2C-2BF	6	1/4	38×13×—	1 1/2×1/2×—	3/8-24UNF(M)	15,000	90	3 35/64	188	7 13/32	0.7	1.5	0.40	14.1	9.5	3/8
FA-2C-3	6	1/4	38×13×—	1 1/2×1/2×—	W3/8-16(M)	15,000	90	3 35/64	157	6 3/16	0.6	1.3	0.40	14.1	9.5	3/8
FA-2C-3BF	6	1/4	38×13×—	1 1/2×1/2×—	W3/8-16(M)	15,000	90	3 35/64	188	7 13/32	0.7	1.5	0.40	14.1	9.5	3/8

* Air Inlet Thread Size...PT or NPT 1/4".

The performance figures are at 0.63MPa (6.3bar).

Refer to "The Instructions and Warning for Safety Use" enclosed in each tool box.

FUJI AIR TOOLS CO., LTD.

2-1-14 Kamiji, Higashinari-ku, Osaka 537-0003, Japan

Tel : 81-6-6972-2335

Fax : 81-6-6972-2250



