



FA-67 Series

Angle Grinders & Cutters



- **Compact:** One of the most compact 7-inch grinder delivering more than 2Hp
- **Industry proof:** improved bevel gear and motor for extended lifetime

The new FA-67 series regroups all Fuji knowledge to drive 7 inch grinding wheels in any conditions. The governed motor delivers great power (2.1hp) giving one of the best productivity on the market. We also have exceptional durability with air cooled and lubricated bevel gears. All these benefits are regrouped in a compact and lightweight body that is easy to operate and responds to any challenges from the heavy metal industries.



FA-67 Series Angle Grinders



Productivity:

2.1 Hp governed motor is maintaining the rotation speed for optimal grinding performance in any condition



Compact & Light weight:

Similar power as heavy duty 7-inch grinders but with 25% less weight and 15% smaller



Durability:

Full metal housing to support any work condition
Helical bevel gear air cooled and lubricated by air oil to handle the power



FA-67-1



FA-67-8F



FA-67-9F



FA-67-9



FA-67-21



FA-67-23

SPECIFICATIONS

| Model | Part Number | Throttle Type | Max Dia. (Wheel Size) | | Spindle Thread | Free Speed | Power | | Overall Length | | Weight | | Max. Air Consumption | | Vibration ISO-28927-1 | | Inlet |
|---------------|-------------|----------------|-----------------------|-----------------|----------------|------------|-------|-----|----------------|------|--------|-----|----------------------|------|-----------------------|----------|---------|
| | | | mm | in | | rpm | W | hp | mm | in | kg | lb | m³/min | cfm | a (m/s²) | k (m/s²) | in |
| Grinders | | | | | | | | | | | | | | | | | |
| FA-67-1 | 5412106204 | Roll | 180 x 6 x 22 | 7 x 1/4 x 0.866 | W1/2-16 | 7600 | 1600 | 2.1 | 229 | 9.0 | 2.5 | 5.5 | 1.6 | 56.5 | 5.5 | 3.5 | 3/8 PT |
| FA-67-8F N EC | 5412106205 | Lock-off Lever | 180 x 6 x 22.2 | 7 x 1/4 x 7/8 | 5/8-11UNC(M) | 7600 | 1500 | 2.0 | 280 | 11.0 | 2.9 | 6.4 | 1.5 | 53.0 | 5.4 | 3.2 | 3/8 NPT |
| FA-67-9 N | 5412106206 | Roll | 180 x 6 x 22.2 | 7 x 1/4 x 7/8 | 5/8-11UNC(M) | 7000 | 1600 | 2.1 | 229 | 9.0 | 2.5 | 5.5 | 1.5 | 53.0 | 4.8 | 3.1 | 3/8 NPT |
| FA-67-9F N EC | 5412106207 | Lock-off Lever | 180 x 6 x 22.2 | 7 x 1/4 x 7/8 | 5/8-11UNC(M) | 7000 | 1500 | 2.0 | 280 | 11.0 | 2.9 | 6.4 | 1.4 | 49.4 | 4.9 | 3.1 | 3/8 NPT |
| Cutters | | | | | | | | | | | | | | | | | |
| FA-67-21 | 5412106208 | Roll | 180 x 2 x 25.4 | 7 x 5/16 x 1 | W1/2-16 | 7600 | 1600 | 2.1 | 229 | 9.0 | 2.5 | 5.5 | 1.6 | 56.5 | 5.5 | 3.5 | 3/8 PT |
| FA-67-23 | 5412106209 | Roll | 180 x 3 x 22 | 7 x 1/8 x 0.866 | W1/2-16 | 7600 | 1600 | 2.1 | 229 | 9.0 | 2.6 | 5.7 | 1.6 | 56.5 | 5.5 | 3.5 | 3/8 PT |

* Air hose size: 12.7mm, 1/2"

* All models: Sound pressure 90 dB(A), Sound Power 101 dB(A)

* All models are side exhaust

* Lock-off Lever throttle type models: CE certified models

Fuji Authorized Distributor:



www.fujitools.com